(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 9 June 2005 (09.06.2005)

PCT

(10) International Publication Number WO 2005/052525 A2

(51) International Patent Classification7:

G01K

(21) International Application Number:

PCT/US2004/038939

(22) International Filing Date:

19 November 2004 (19.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/523,779

20 November 2003 (20.11.2003) U

(71) Applicants and

(72) Inventors: NICOL, William A. [US/US]; 2299 Pine Drive, Douglasville, GA 30135 (US). KACHNIC, Edward [US/US]; 4026 Hickory Nut Drive, Douglasville, GA 30135 (US). PRYHODA, Benjamin [US/US]; 530 Arbor Drive, Lafayette, CO 80026 (US).

- (74) Agent: SOVINSKI, Sandra; Myers & Kaplan, Intellectual Property Law LLC, 1899 Powers Ferry Road, Suite 310, Atlanta, GA 30339 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: SENSORY SYSTEM AND METHOD THEREOF

Optimum Election Temperature

= Cooling Time

Start

Start

Start

Start

Start

Start

Start

Start

Model Open Signed

Activates

R Image Capture

Vision

Controller

Determines

Temperature

Testermines

Temperature

Coutside Surface Temperature

Outside Surface Temperature

(57) Abstract: A sensory system and method for optimizing the cycle time of a part-forming process, wherein the temperature status of a molded part is ascertained and utilized to enable minimization of mold close time.

WO 2005/052525 A2



FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

 without international search report and to be republished upon receipt of that report